



EJE 50



EJE 35/40

EJE 35 / 40 / 50

(AC Drive)
Electric Pedestrian Pallet Truck
(3500 / 4000 / 5000 kg.)

- MOSFET Programmable Step-less Speed Controller
- Fully-integrated AC Traction System
- Heavy Duty Design.
- Multi-function tiller head with enhanced Safety.
- Ergonomically designed for enhanced Productivity, Safety & Serviceability

The Jost's heavy duty Electric Pedestrian Pallet Truck, type EJE has been designed specially for flexible handling of palletised loads for increased performance as well as long usage times. The EJE is designed particularly for heavy duty requirements of lorry loading / unloading. Jost's Pallet Trucks with AC technology provides additional advantage of reduced maintenance, improved power utilisation and improved battery life.



OPERATOR AREA:

The low hinged handle provide ample scope for greater maneuverability. The enclosed design feature, toe guard, safety and emergency stop buttons provide maximum safety for the operator.



DRIVE & DRIVE CONTROL

Powerful 1.5 / 2.5 Kw high performance AC motor of 1 hour rating, efficiently drives a low noise, two stage compact gear unit mounted directly on to the drive wheel. The Microprocessor based MOSFET controller provide smooth and step-less control of speed and acceleration. It also helps in obtaining fault diagnostic information quickly and easily.



CHASSIS

Robust Construction and the stable five point contact design enhances stability during turning. The swivel side support wheels provide stability during travel and permits safe maneuvering in confined spaces. The battery holding compartment in the chassis is provided with suitable roller bed for easy removal of the battery.



WHEELS

The polyurethane wheels configuration enable noiseless smooth ride and have better ability to withstand impact loads while rolling over bumps on the surfaces. The tandem load wheel configuration ensures smooth roll over with continuous contact on the floor and enables easy negotiation without jerks.



TILLER HEAD & STEERING:

Multi-function tiller head with ergonomically arranged operating elements for travel, lift, lowering and horn at finger tips provide highest operator comfort and safety. It also has a belly button that provides additional safety in case of emergencies. Steering lock at 90° on either side and can be operated only in limited range of handle inclinations comfortable to operator. This provides additional operational safety.



FORKS

Robust steel fabricated forks ensure long lasting and durable service. Various options of fork lengths and with width over forks are available for different types of pallets. The fork ends are suitably tapered to provide better maneuverability while turning in confined spaces.



BRAKE

Electromagnetic disc brake with hard wearing, asbestos free liner provides instantaneous braking. When the handle is close to vertical or horizontal position, the brake becomes operational with simultaneous power cut-off.



HYDRAULIC SYSTEM

Compact power pack unit with high pressure pump driven by 0.8 / 2.2 Kw sturdy compound wound motor operates the lifting mechanism comprising of low lift hydraulic cylinder and load wheel linkages and for jerk free lift of the loaded pallet for the required ground clearance. The compact system consumes less battery power and is designed with very little scope for hydraulic losses.



SAFETY

The truck is equipped with automatic lift cut off at 80% battery discharge condition for enhanced safety, emergency power cut-off switch on chassis panel and anti-collision switch on tiller head. The hydraulic circuit has safety feature like pressure relief valves and non return valves. The toe guard at the rear, guards the operator against inadvertent accidents. EJE 50 is equipped with pressure compensated flow control valve for cushioning effect while lowering of loaded forks.



SERVICING

The modular service friendly design with easily removable front cover provides easy access to all components for servicing thus saving valuable time during maintenance



BATTERY & CHARGER

The equipment comes with 24V / 330Ah traction battery to ensure steady power supply. High frequency constant current automatic charger of 24V / 35Amp is supplied as a standard.

Specification

Model	Nos.	EJE 35	EJE 40	EJE 50																																																																
Drive	type	AC	AC	AC																																																																
Capacity	Q = Kg.	3500	4000	5000																																																																
Load Center for rated capacity	C = mm	600	600	600																																																																
Load distance (from load wheel to fork face)	L2 = mm	870	870	760																																																																
Travel speed (min.), laden	kmph	4.0	4.0	4.5																																																																
Travel speed, unladen	kmph	4.5	4.5	6.5																																																																
Lift speed, laden / unladen	cm/s	1.6 / 2.5	1.4 / 2.5	2.2 / 2.5																																																																
Lowering speed, laden / unladen	cm/s	3.1 / 2.5	3.3 / 2.5	3.3 / 2.3																																																																
Gradient performance, laden / unladen	%	6 / 16	5 / 16	3 / 16																																																																
Battery weight, apx.	Kg.	310	310	310																																																																
Service weight incl. 'battery, apx.	Kg.	790	810	850																																																																
Wheelbase	Y = mm	1570	1570	1460																																																																
Wheels	type	Polyurethane	Polyurethane	Polyurethane																																																																
Load Wheel	mm	Ø85x75W	Ø85x75W	Ø100x140W																																																																
Side support castor wheel	mm	Ø100x40W	Ø100x40W	Ø100x40W																																																																
Drive wheel	mm	Ø200x85W	Ø200x85W	Ø254x100W																																																																
Wheels, number front / rear (x = driven wheels)	nos.	1x + 2 / 4	1x + 2 / 4	1x + 2 / 4																																																																
Track width, front / rear	B2 / S = mm	606 / 385	606 / 385	666 / 440																																																																
Overall length	L = mm	2020	2020	1920																																																																
Lift	h1 = mm	115	115	125																																																																
Fork lowered height	h = mm	90	90	110																																																																
Safety clearance	a = mm	100	100	Front overhang	G = mm	264	264	270	Overall width	B1 = mm	850	850	850	Fork dimensions	s/e/l = mm	65/185/1150	65/185/1150	80/240/1150	Load Wheel / Forks tip distance	X = mm	186	186	190	Width over forks (WOF)	m = mm	570	570	680	Ground clearance (Center of wheel base)	GC = mm	35	35	30	Turning radius	Wa = mm	1900	1900	1800	Drive control	type	Mosfet	Mosfet	Mosfet	Drive motor rating	kW	1.5	1.5	2.5	S2 = 60 min.					Lift motor rating	kW	0.8	0.8	2.2	S2 = 1.8 min., S3 = 7%					Sound level at driver's ear	db(A)	85	85	85
Front overhang	G = mm	264	264	270																																																																
Overall width	B1 = mm	850	850	850																																																																
Fork dimensions	s/e/l = mm	65/185/1150	65/185/1150	80/240/1150																																																																
Load Wheel / Forks tip distance	X = mm	186	186	190																																																																
Width over forks (WOF)	m = mm	570	570	680																																																																
Ground clearance (Center of wheel base)	GC = mm	35	35	30																																																																
Turning radius	Wa = mm	1900	1900	1800																																																																
Drive control	type	Mosfet	Mosfet	Mosfet																																																																
Drive motor rating	kW	1.5	1.5	2.5																																																																
S2 = 60 min.																																																																				
Lift motor rating	kW	0.8	0.8	2.2																																																																
S2 = 1.8 min., S3 = 7%																																																																				
Sound level at driver's ear	db(A)	85	85	85																																																																


Working Aisle Width Ast. incl 200mm safety clearance

Pallet size c x b	Position		3500 kg	4000 kg	5000 kg
800 x 1200	Crosswise	mm	2400	2400	2350
800 x 1200	Lengthways	mm	2550	2550	2450
1000 x 1200	Crosswise	mm	2400	2400	2550
1000 x 1200	Lengthways	mm	2640	2640	2350
1200 x 1200	Lengthways	mm	2740	2740	2650

Note: 90° stacking aisle width.

Optional Fork Lengths and Widths

Capacity (kg)	Fork length (mm)	Width over fork (mm)	
3500	1150	680	750
4000	1150	680	750
3500	1250	680	750
3000	1400	680	750
3000	900	680	750



For any special requirements, Please contact Jost's HO. Dimensions indicated here are subject to variations of ± 20mm and performance ± 10%. Service weight ± 50kg. Right to make changes and technical improvement reserved.



Since 1907

Jost's Engineering Company Limited

C-7 Wagle Industrial Estate, Road No. 12, Thane - 400 604. Maharashtra. INDIA.

T.: +91.22.6117 4000 / 2582 1748 F.: +91.22.6117 4020 E.: infomhe@josts.in

Bengaluru : +91.080.41234775 / 41234885 Chennai : +91.044.2626 8536 / 2628 8407 Delhi : +91.011. 4567.6000 / 4567.6014 Kolkata : +91.033.2242 9510 / 4008 1242 Pune : +91.020.2543. 4565/2543 .4390 Secunderabad : +91.040.2771.4934 / 44 / 54 Vadodara : +91.0265.2351.642